COMMUNICATIONS RESOURCE AVAILABILITY WORKSHEET

Frequency Band	Description
Amateur 6m / HF	HF Voice / Digital / Winlink

Pg No	Channel Configuration	Channel Name/Trunked Radio System Talkgroup	Eligible Users	RX Freq N or W	RX Tone/NAC	TX Freq N or W	Tx Tone/NAC	Mode A, D or M	Remarks
	LSB	ARES Primary Night	HAM	3.9400		3.9400		A	Primary HF Night
	LSB	ARES Primary Day	HAM	7.2620		7.2620		A	Primary HF Day
	LSB	Alt HF Night	HAM	3.8600		3.8600		A	Alternate HF Night
	USB	Alt HF Day	HAM	28.4550		28.4550		A	Alternate HF Day
	USB-D	Digital HF Night	HAM	3.5830		3.5830		D	HF Digital Night (NBEMS)
	USB-D	Digital HF Day	HAM	7.0710		7.0710		D	HF Digital Day (NBEMS)
	FM	SW 6m Coord	HAM	52.5250		52.5250		A	Statewide Coordination 6m
		WInlink via CMS	HAM	HF or PACKET		HF or PACKET			

The convention calls for frequency lists to show four digits after the decimal place, followed by either an “N” or a “W”, depending on whether the frequency is narrow or wide band. Mode refers to either “A” or “D” indicating analog or digital (e.g. Project 25) or "M" indicating mixed mode. All channels are shown as if programmed in a control station, mobile or portable radio. Repeater and base stations must be programmed with the Rx and Tx reversed.